SAFETY DATA SHEET

127345



1. Identification

Product number 1000000897

Product identifier FAST TACK FOAM & FABRIC ADHESIVE

Company information Sprayway, Inc.

1005 S. Westgate Drive

Addison, IL 60101 United States

General Assistance 1-630-628-3000 Company phone

Emergency telephone US Emergency telephone outside 1-866-836-8855

US

1-952-852-4646

01 Version #

Adhesive

Recommended use Recommended restrictions None known.

2. Hazard(s) identification

Physical hazards Flammable aerosols Category 1 Category 2 **Health hazards** Skin corrosion/irritation

Serious eye damage/eye irritation Category 2A Reproductive toxicity (fertility) Category 2

Specific target organ toxicity, single exposure Category 3 narcotic effects

Specific target organ toxicity, repeated

exposure

Aspiration hazard Category 1

Not classified. **Environmental hazards OSHA** defined hazards Not classified.

Label elements



Signal word Danger

Hazard statement Extremely flammable aerosol. May be fatal if swallowed and enters airways. Causes skin irritation.

Causes serious eye irritation. May cause drowsiness or dizziness. Suspected of damaging fertility.

Category 2

May cause damage to organs through prolonged or repeated exposure.

Precautionary statement

Storage

Obtain special instructions before use. Do not handle until all safety precautions have been read Prevention

and understood. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use. Do not breathe mist or vapor, Wash thoroughly after handling. Use only outdoors or in a well-ventilated area. Wear protective gloves/protective clothing/eye protection/face

protection.

Response If swallowed: Immediately call a poison center/doctor. If on skin: Wash with plenty of water. If

inhaled: Remove person to fresh air and keep comfortable for breathing. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If exposed or concerned: Get medical advice/attention. Call a poison center/doctor if you feel unwell. Specific treatment (see this label). Do NOT induce vomiting. If skin irritation occurs: Get medical advice/attention. If eye irritation persists: Get medical

advice/attention. Take off contaminated clothing and wash before reuse. Collect spillage.

Store in a well-ventilated place. Keep container tightly closed. Store locked up. Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.

Dispose of contents/container in accordance with local/regional/national/international regulations. **Disposal**

Hazard(s) not otherwise classified (HNOC)

None known.

Supplemental information

None.

3. Composition/information on ingredients

Mixtures

Chemical name	Common name and synonyms	CAS number	%
Acetone		67-64-1	10 - 20
Butane		106-97-8	10 - 20
n-Hexane		110-54-3	10 - 20
Propane		74-98-6	10 - 20
2-Methylpentane		107-83-5	2.5 - 10
Methyl Acetate		79-20-9	2.5 - 10
3-Methylpentane		96-14-0	1 - 2.5
Cyclohexane		110-82-7	1 - 2.5
Other components below reportable levels	3		10 - 20

^{*}Designates that a specific chemical identity and/or percentage of composition has been withheld as a trade secret.

4. First-aid measures

Inhalation Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON

CENTER or doctor/physician if you feel unwell.

Skin contact Remove contaminated clothing. Wash with plenty of soap and water. If skin irritation occurs: Get

medical advice/attention. Wash contaminated clothing before reuse.

Eye contactImmediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if

present and easy to do. Continue rinsing. Get medical attention if irritation develops and persists.

Call a physician or poison control center immediately. Rinse mouth. Do not induce vomiting. If

vomiting occurs, keep head low so that stomach content doesn't get into the lungs.

Most important symptoms/effects, acute and delayed

Ingestion

May cause drowsiness and dizziness. Headache. Nausea, vomiting. Irritation of nose and throat. Aspiration may cause pulmonary edema and pneumonitis. Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Skin irritation. May cause redness and pain. Prolonged exposure may cause chronic effects.

Indication of immediate medical attention and special treatment needed

General information

Provide general supportive measures and treat symptomatically. Keep victim under observation. Symptoms may be delayed.

(show the labe involved, and t

IF exposed or concerned: Get medical advice/attention. If you feel unwell, seek medical advice (show the label where possible). Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Show this safety data sheet to the doctor in attendance.

5. Fire-fighting measures

Suitable extinguishing media Alcohol r
Unsuitable extinguishing Do not u

Alcohol resistant foam. Water fog. Dry chemical powder. Carbon dioxide (CO2).

Do not use water jet as an extinguisher, as this will spread the fire.

media
Specific hazards arising from the chemical

Contents under pressure. Pressurized container may explode when exposed to heat or flame.

Special protective equipment and precautions for firefighters

Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA.

and precautions for firefighter Fire-fighting

Move containers from fire area if you can do so without risk. Containers should be cooled with water to prevent vapor pressure build up. For massive fire in cargo area, use unmanned hose holder or monitor nozzles, if possible. If not, withdraw and let fire burn out.

Specific methods

equipment/instructions

Use standard firefighting procedures and consider the hazards of other involved materials. Move containers from fire area if you can do so without risk. In the event of fire and/or explosion do not

breathe fumes.

General fire hazards Extremely flammable aerosol.

Product name: FAST TACK FOAM & FABRIC ADHESIVE
Product #: 1000000897 Version #: 01 Issue date: 05-30-2015

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Keep out of low areas. Wear appropriate protective equipment and clothing during clean-up. Do not breathe mist or vapor. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate closed spaces before entering them. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.

Methods and materials for containment and cleaning up

Refer to attached safety data sheets and/or instructions for use. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Keep combustibles (wood, paper, oil, etc.) away from spilled material. Stop leak if you can do so without risk. Move the cylinder to a safe and open area if the leak is irreparable. Cover with plastic sheet to prevent spreading. Absorb in vermiculite, dry sand or earth and place into containers. Prevent entry into waterways, sewer, basements or confined areas. Following product recovery, flush area with water.

Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination. For waste disposal, see section 13 of the SDS.

Environmental precautions

Avoid release to the environment. Inform appropriate managerial or supervisory personnel of all environmental releases. Prevent further leakage or spillage if safe to do so. Avoid discharge into drains, water courses or onto the ground.

7. Handling and storage

Precautions for safe handling

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Pressurized container: Do not pierce or burn, even after use. Do not use if spray button is missing or defective. Do not spray on a naked flame or any other incandescent material. Do not smoke while using or until sprayed surface is thoroughly dry. Do not cut, weld, solder, drill, grind, or expose containers to heat, flame, sparks, or other sources of ignition. All equipment used when handling the product must be grounded. Do not re-use empty containers. Do not breathe mist or vapor. Avoid contact with eyes, skin, and clothing. Avoid prolonged exposure. Use only in well-ventilated areas. Should be handled in closed systems, if possible. Pregnant or breastfeeding women must not handle this product. Wear appropriate personal protective equipment. Wash hands thoroughly after handling. Avoid release to the environment. Observe good industrial hygiene practices.

Conditions for safe storage, including any incompatibilities

Level 3 Aerosol.

Store locked up. Pressurized container. Protect from sunlight and do not expose to temperatures exceeding 50°C/122°F. Do not puncture, incinerate or crush. Do not handle or store near an open flame, heat or other sources of ignition. This material can accumulate static charge which may cause spark and become an ignition source. Refrigeration recommended. Store away from incompatible materials (see Section 10 of the SDS). Level 3 Aerosol.

****/al...a

8. Exposure controls/personal protection

Occupational exposure limits

US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

Components	Туре	Value	
Acetone (CAS 67-64-1)	PEL	2400 mg/m3	
		1000 ppm	
Cyclohexane (CAS 110-82-7)	PEL	1050 mg/m3	
		300 ppm	
Methyl Acetate (CAS 79-20-9)	PEL	610 mg/m3	
,		200 ppm	
n-Hexane (CAS 110-54-3)	PEL	1800 mg/m3	
		500 ppm	
Propane (CAS 74-98-6)	PEL	1800 mg/m3	
, ,		1000 ppm	
US. ACGIH Threshold Limit Value	s		
Components	Туре	Value	
2-Methylpentane (CAS 107-83-5)	STEL	1000 ppm	
	TWA	500 ppm	
3-Methylpentane (CAS 96-14-0)	STEL	1000 ppm	

Product name: FAST TACK FOAM & FABRIC ADHESIVE

Product #: 1000000897 Version #: 01 Issue date: 05-30-2015 3 / 12

US.	ACGIH	Threshold	Limit Values
-----	--------------	-----------	---------------------

Components	Туре	Value
	TWA	500 ppm
Acetone (CAS 67-64-1)	STEL	750 ppm
	TWA	500 ppm
Butane (CAS 106-97-8)	STEL	1000 ppm
Cyclohexane (CAS 110-82-7)	TWA	100 ppm
Methyl Acetate (CAS 79-20-9)	STEL	250 ppm
	TWA	200 ppm
n-Hexane (CAS 110-54-3)	TWA	50 ppm
US. NIOSH: Pocket Guide to Cher	nical Hazards	
Components	Туре	Value
Acetone (CAS 67-64-1)	TWA	590 mg/m3
		250 ppm
Butane (CAS 106-97-8)	TWA	1900 mg/m3
		800 ppm
Cyclohexane (CAS 110-82-7)	TWA	1050 mg/m3
		300 ppm
Methyl Acetate (CAS 79-20-9)	STEL	760 mg/m3
		250 ppm
	TWA	610 mg/m3
		200 ppm
n-Hexane (CAS 110-54-3)	TWA	180 mg/m3
		50 ppm
Propane (CAS 74-98-6)	TWA	1800 mg/m3
		1000 ppm

Biological limit values

ACGIH	Biological	Exposure	Indices

Components	Value	Determinant	Specimen	Sampling Time
Acetone (CAS 67-64-1)	50 mg/l	Acetone	Urine	*
n-Hexane (CAS 110-54-3)	0.4 mg/l	2,5-Hexanedio n, without hydrolysis	Urine	*

^{* -} For sampling details, please see the source document.

Exposure guidelines

US - California OELs: Skin designation

n-Hexane (CAS 110-54-3) Can be absorbed through the skin.

US ACGIH Threshold Limit Values: Skin designation

n-Hexane (CAS 110-54-3)

Can be absorbed through the skin.

Appropriate engineering

controls

Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Eye wash facilities and emergency shower must be available when handling this product.

Individual protection measures, such as personal protective equipment

Eye/face protection Chemical respirator with organic vapor cartridge and full facepiece.

Hand protection Wear appropriate chemical resistant gloves.

Skin protection

Other Wear appropriate chemical resistant clothing. Use of an impervious apron is recommended.

Skin protection

Respiratory protection Chemical respirator with organic vapor cartridge and full facepiece.

Thermal hazards Wear appropriate thermal protective clothing, when necessary.

General hygiene considerations

When using, do not eat, drink or smoke. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.

9. Physical and chemical properties

Appearance

Physical state Gas.
Form Aerosol.
Color Not available.
Odor Not available.
Odor threshold Not available.
pH Not available.
Melting point/freezing point Not available.

Initial boiling point and boiling

204.84 °F (96.02 °C) estimated

range

Flash point -156.0 °F (-104.4 °C) Propellent estimated

Evaporation rate Not available.

Flammability (solid, gas) Not available.

Upper/lower flammability or explosive limits

Flammability limit - lower

2.1 % estimated

(%)

Flammability limit - upper

9.6 % estimated

(%)

Explosive limit - lower (%) Not available.

Explosive limit - upper (%) Not available.

Vapor pressure 52 psig @70F estimated

Vapor density Not available.

Relative density Not available.

Solubility(ies)

Solubility (water) Not available.

Partition coefficient Not available.

(n-octanol/water)

Auto-ignition temperature 632.7 °F (333.72 °C) estimated

Decomposition temperatureNot available. **Viscosity**Not available.

Other information

Specific gravity 0.715 estimated

10. Stability and reactivity

ReactivityThe product is stable and non-reactive under normal conditions of use, storage and transport.

Chemical stability Material is stable under normal conditions.

Possibility of hazardous Hazardous polymerization does not occur.

reactions

Conditions to avoid

Avoid temperatures exceeding the flash point. Contact with incompatible materials.

Incompatible materialsStrong oxidizing agents. Nitrates. Fluorine. Chlorine.Hazardous decompositionNo hazardous decomposition products are known.

products

11. Toxicological information

Information on likely routes of exposure

Ingestion Droplets of the product aspirated into the lungs through ingestion or vomiting may cause a serious

chemical pneumonia.

Inhalation May cause damage to organs through prolonged or repeated exposure by inhalation. May cause

drowsiness and dizziness. Headache. Nausea, vomiting. Prolonged inhalation may be harmful.

Product name: FAST TACK FOAM & FABRIC ADHESIVE
Product #: 1000000897 Version #: 01 Issue date: 05-30-2015

Skin contact Causes skin irritation.

Eye contact Causes serious eye irritation.

Symptoms related to the physical, chemical and toxicological characteristics

May cause drowsiness and dizziness. Headache. Nausea, vomiting. Irritation of nose and throat. Aspiration may cause pulmonary edema and pneumonitis. Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Skin irritation. May cause redness and pain.

Information on toxicological effects

Acute toxicity	te toxicity May be fatal if swallowed and enters airways. Narcotic effects.		
Components	Species	Test Results	
Acetone (CAS 67-64-1)			
Acute			
Dermal			
LD50	Guinea pig	> 7426 mg/kg, 24 Hours	
		> 9.4 ml/kg, 24 Hours	
	Rabbit	> 7426 mg/kg, 24 Hours	
		> 9.4 ml/kg, 24 Hours	
Inhalation		-	
LC50	Rat	55700 ppm, 3 Hours	
		132 mg/l, 3 Hours	
		50.1 mg/l	
Oral		30.1 mg/l	
LD50	Rat	5800 mg/kg	
2000	Nat	2.2 ml/kg	
D 1 (0.40, 400, 07.0)		2.2 IIII/kg	
Butane (CAS 106-97-8)			
Acute			
Inhalation LC50	Mouse	1237 mg/l, 120 Minutes	
2030	Wouse		
	5.4	52 %, 120 Minutes	
	Rat	1355 mg/l	
Cyclohexane (CAS 110-82-7)			
Acute			
Dermal	Dakkii	0000	
LD50	Rabbit	> 2000 mg/kg	
Inhalation	Det	20000	
LC50	Rat	> 32880 mg/m3, 4 Hours	
		> 5540 ppm, 4 Hours	
Methyl Acetate (CAS 79-20-9)			
Acute			
Dermal	D./	0000	
LD50	Rat	> 2000 mg/kg, 24 Hours	
Inhalation	D 11.11	22.4	
LC100	Rabbit	98.4 mg/l, 4 Hours	
Oral	D./	0.400	
LD50	Rat	6482 mg/kg	
n-Hexane (CAS 110-54-3)			
Acute			
Dermal LD50	Dobbit	> 2000 mm/lim Allows	
LD50	Rabbit	> 2000 mg/kg, 4 Hours	
		> 5 ml/kg, 4 Hours	
Inhalation			
LC50	Rat	> 5000 ppm, 24 Hours	

Product name: FAST TACK FOAM & FABRIC ADHESIVE

Product #: 1000000897 Version #: 01 Issue date: 05-30-2015

Components	Species	Test Results
		> 31.86 mg/l
		73860 ppm, 4 Hours
Oral		
LD50	Rat	24 ml/kg
		24 g/kg
	Wistar rat	49 g/kg
Propane (CAS 74-98-6)		
Acute		
Inhalation		
LC50	Mouse	1237 mg/l, 120 Minutes
		52 %, 120 Minutes
	Rat	1355 mg/l
		658 mg/l/4h

^{*} Estimates for product may be based on additional component data not shown.

Causes skin irritation. Skin corrosion/irritation

Serious eye damage/eye

Causes serious eye irritation.

irritation

Respiratory or skin sensitization

Respiratory sensitization Not available.

Skin sensitization This product is not expected to cause skin sensitization.

No data available to indicate product or any components present at greater than 0.1% are Germ cell mutagenicity

mutagenic or genotoxic.

This product is not considered to be a carcinogen by IARC, ACGIH, NTP, or OSHA. Carcinogenicity

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not listed.

Reproductive toxicity Suspected of damaging fertility.

Specific target organ toxicity -

single exposure

May cause drowsiness and dizziness.

Specific target organ toxicity -

repeated exposure

May cause damage to organs through prolonged or repeated exposure. Respiratory system.

Central nervous system. Eyes. Peripheral nervous system. Skin.

Aspiration hazard May be fatal if swallowed and enters airways.

Chronic effects Prolonged inhalation may be harmful. May cause damage to organs through prolonged or

repeated exposure.

12. Ecological information

Ecotoxicity Toxic to aquatic life with long lasting effects.

	Species	Test Results
EC50	Water flea (Daphnia magna)	21.6 - 23.9 mg/l, 48 hours
LC50	Rainbow trout,donaldson trout (Oncorhynchus mykiss)	4740 - 6330 mg/l, 96 hours
-82-7)		
LC50	Fathead minnow (Pimephales promelas)	23.03 - 42.07 mg/l, 96 hours
-20-9)		
IC50	Algae	120.0001 mg/L, 72 Hours
EC50	Daphnia	1026.7 mg/L, 48 Hours
LC50	Fathead minnow (Pimephales promelas)	295 - 348 mg/l, 96 hours
	LC50 82-7) LC50 -20-9) IC50 EC50	EC50 Water flea (Daphnia magna) LC50 Rainbow trout,donaldson trout (Oncorhynchus mykiss) 82-7) LC50 Fathead minnow (Pimephales promelas) -20-9) IC50 Algae EC50 Daphnia

Product name: FAST TACK FOAM & FABRIC ADHESIVE

SDS US Product #: 1000000897 Version #: 01 Issue date: 05-30-2015

Components Species Test Results

n-Hexane (CAS 110-54-3)

Aquatic

Fish LC50 Fathead minnow (Pimephales promelas) 2.101 - 2.981 mg/l, 96 hours

Persistence and degradability No data is available on the degradability of this product.

Bioaccumulative potential No data available.

Partition coefficient n-octanol / water (log Kow)

2-Methylpentane	3.74
3-Methylpentane	3.6
Acetone	-0.24
Butane	2.89
Cyclohexane	3.44
Methyl Acetate	0.18
n-Hexane	3.9
Propane	2.36

Mobility in soil No data available.

Other adverse effects No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation

potential, endocrine disruption, global warming potential) are expected from this component.

13. Disposal considerations

Disposal instructionsCollect and reclaim or dispose in sealed containers at licensed waste disposal site. Contents

under pressure. Do not puncture, incinerate or crush. Do not allow this material to drain into sewers/water supplies. Do not contaminate ponds, waterways or ditches with chemical or used container. Dispose of contents/container in accordance with local/regional/national/international

regulations.

Local disposal regulations Dispose in accordance with all applicable regulations.

Hazardous waste code

The waste code should be assigned in discussion between the user, the producer and the waste

disposal company.

US RCRA Hazardous Waste U List: Reference

Acetone (CAS 67-64-1) U002 Cyclohexane (CAS 110-82-7) U056

Waste from residues / unused

products

Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see:

Disposal instructions).

Contaminated packaging Empty containers should be taken to an approved waste handling site for recycling or disposal.

Since emptied containers may retain product residue, follow label warnings even after container is

emptied. Do not re-use empty containers.

14. Transport information

DOT

UN number UN1950

UN proper shipping name

Transport hazard class(es)

Aerosols, flammable

Class 2.1 Subsidiary risk -Label(s) 2.1

Packing group Not applicable.

Special precautions for user Read safety instructions, SDS and emergency procedures before handling. Read safety

instructions, SDS and emergency procedures before handling.

Special provisionsN82Packaging exceptions306Packaging non bulkNonePackaging bulkNone

This product meets the exception requirements of section 173.306 as a limited quantity and may be shipped as a limited quantity. Until 12/31/2020, the "Consumer Commodity - ORM-D" marking may still be used in place of the new limited quantity diamond mark for packages of UN 1950 Aerosols. Limited quantities require the limited quantity diamond mark on cartons after 12/31/20 and may be used now in place of the "Consumer Commodity ORM-D" marking and both may be displayed concurrently.

^{*} Estimates for product may be based on additional component data not shown.

IATA

UN number UN1950

UN proper shipping name Aerosols, flammable

Transport hazard class(es)

Class 2.1 Subsidiary risk -Label(s) 2.1

Packing group Not applicable.

Environmental hazards Yes ERG Code 10L

Special precautions for user Read safety instructions, SDS and emergency procedures before handling. Read safety

instructions, SDS and emergency procedures before handling.

Other information

Passenger and cargo

aircraft

Allowed.

Cargo aircraft only Allowed.

Packaging Exceptions LTD QTY

IMDG

UN number UN1950 **UN proper shipping name** AEROSOLS

Transport hazard class(es)

Class 2.1 Subsidiary risk -Label(s) 2.1

Packing group Not applicable.

Environmental hazards

Marine pollutant Yes EmS F-D, S-U

Special precautions for user Read safety instructions, SDS and emergency procedures before handling. Read safety

instructions, SDS and emergency procedures before handling.

Packaging Exceptions

Transport in bulk according to

Annex II of MARPOL 73/78 and

the IBC Code

LTD QTY Not applicable.

DOT



IATA; IMDG



Marine pollutant



General information

IMDG Regulated Marine Pollutant.

15. Regulatory information

US federal regulations

This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication

Standard, 29 CFR 1910.1200.

All components are on the U.S. EPA TSCA Inventory List.

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

CERCLA Hazardous Substance List (40 CFR 302.4)

Acetone (CAS 67-64-1)

Cyclohexane (CAS 110-82-7)

n-Hexane (CAS 110-54-3)

Listed.

Listed.

SARA 304 Emergency release notification

Not regulated.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not listed.

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Hazard categories Immediate Hazard - Yes

Delayed Hazard - Yes Fire Hazard - Yes Pressure Hazard - Yes Reactivity Hazard - No

SARA 302 Extremely hazardous substance

Chemical name	CAS number	Reportable quantity	Threshold planning quantity	Threshold planning quantity, lower value	Threshold planning quantity, upper value	
Phenol	108-95-2	1000		500 lbs	10000 lbs	

SARA 311/312 Hazardous No

chemical

SARA 313 (TRI reporting)

CAS number	% by wt.	
110-54-3	10 - 20	
110-82-7	1 - 2.5	
67-56-1	0.1 - 1	
75-07-0	0.01 - 0.1	
100-41-4	0.01 - 0.1	
100-42-5	0.01 - 0.1	
	110-54-3 110-82-7 67-56-1 75-07-0 100-41-4	110-54-3 110-82-7 67-56-1 75-07-0 100-41-4 10 - 20 1 - 2.5 0.1 - 1 0.01 - 0.1

Other federal regulations

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

n-Hexane (CAS 110-54-3)

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Butane (CAS 106-97-8) Propane (CAS 74-98-6)

Safe Drinking Water Act

Not regulated.

(SDWA)

Drug Enforcement Administration (DEA). List 2, Essential Chemicals (21 CFR 1310.02(b) and 1310.04(f)(2) and Chemical Code Number

Acetone (CAS 67-64-1) 6532

Product name: FAST TACK FOAM & FABRIC ADHESIVE
Product #: 1000000897 Version #: 01 Issue date: 05-30-2015

Drug Enforcement Administration (DEA). List 1 & 2 Exempt Chemical Mixtures (21 CFR 1310.12(c))

Acetone (CAS 67-64-1) 35 %WV

DEA Exempt Chemical Mixtures Code Number

Acetone (CAS 67-64-1) 6532

US state regulations

US. Massachusetts RTK - Substance List

2-Methylpentane (CAS 107-83-5) 3-Methylpentane (CAS 96-14-0)

Acetone (CAS 67-64-1)

Butane (CAS 106-97-8)

Cyclohexane (CAS 110-82-7)

Methyl Acetate (CAS 79-20-9)

n-Hexane (CAS 110-54-3)

Propane (CAS 74-98-6)

US. New Jersey Worker and Community Right-to-Know Act

2-Methylpentane (CAS 107-83-5)

Acetone (CAS 67-64-1)

Butane (CAS 106-97-8)

Cyclohexane (CAS 110-82-7)

Methyl Acetate (CAS 79-20-9)

n-Hexane (CAS 110-54-3)

Propane (CAS 74-98-6)

US. Pennsylvania Worker and Community Right-to-Know Law

2-Methylpentane (CAS 107-83-5)

3-Methylpentane (CAS 96-14-0)

Acetone (CAS 67-64-1)

Butane (CAS 106-97-8)

Cyclohexane (CAS 110-82-7)

Methyl Acetate (CAS 79-20-9)

n-Hexane (CAS 110-54-3)

Propane (CAS 74-98-6)

US. Rhode Island RTK

Acetone (CAS 67-64-1)

Butane (CAS 106-97-8)

Cyclohexane (CAS 110-82-7)

n-Hexane (CAS 110-54-3)

Propane (CAS 74-98-6)

US. California Proposition 65

WARNING: This product contains a chemical known to the State of California to cause cancer.

US - California Proposition 65 - CRT: Listed date/Carcinogenic substance

Acetaldehyde (CAS 75-07-0) Listed: April 1, 1988 Listed: June 11, 2004 Ethyl Benzene (CAS 100-41-4)

US - California Proposition 65 - CRT: Listed date/Developmental toxin

Methanol (CAS 67-56-1) Listed: March 16, 2012

International Inventories

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Chemical Substances (AICS)	No
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	No
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	No
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	No
Korea	Existing Chemicals List (ECL)	No
New Zealand	New Zealand Inventory	No
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	No

Product name: FAST TACK FOAM & FABRIC ADHESIVE

Product #: 1000000897 Version #: 01 Issue date: 05-30-2015

Country(s) or region Inventory name On inventory (yes/no)*

United States & Puerto Rico Toxic Substances Control Act (TSCA) Inventory

Voc

*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)
A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

16. Other information, including date of preparation or last revision

Issue date 05-30-2015

Version # 01

Disclaimer

We cannot anticipate all conditions under which this information and its product, or the products of other manufacturers in combination with its product, may be used. It is the user's responsibility to ensure safe conditions for handling, storage and disposal of the product, and to assume liability for loss, injury, damage or expense due to improper use. The information in the sheet was written based on the best knowledge and experience currently available. The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

Product name: FAST TACK FOAM & FABRIC ADHESIVE SDS US